

## Technique Data

◆ Sensor	Fuel cell
◆ Measurement range	0-550mg/100ml
◆ Measurement accuracy	0-80mg/100ml : ±5mg/100ml
◆ Measurement time	< 10 seconds
◆ Zeroing time	< 5 seconds
◆ Blow volume	1.0L or according to customer requirement
◆ Display	1.3inch, TFT
◆ Data store	up to 40000 measured value
◆ Real time clock	Yes
◆ Battery	Li-ion, 3.7V, 1200mAh
◆ Calibration	Every 6 months
◆ Operation temperature	0°C to +40°C
◆ Storage temperature	-20°C to +60°C
◆ Dimension	L138mm*W68mm*H30.5mm
◆ Weight	121g

## Product Features

- ◆ Fuel cell sensor
- ◆ Blow volume detection
- ◆ Built-in Li-ion battery
- ◆ 1.3inch TFT display
- ◆ Data storage capability



 **Don't Drink & Drive**

2010  
Breathalyzer



**InterMed**  
**Shenzhen Intermed Co., Ltd**

Tel : +86-755-86372570/71/72

Fax: +86-755-86372573

Email : info@int-med.com

Website: www.int-med.com

Add : 2Fl., Building 64, Majialong Industrial Zone, Daxin Road,  
Nanshan. 518052, Shenzhen, Guangdong, China