

# Product Specifications

## FlashCheck® Min/Max Digital Alarm Thermometer

<b>Measurement Range</b>	-58°F to 158°F (-50°C to 70°C)
<b>Operating Range</b>	14°F to 122°F (-10°C to 50°C)
<b>Accuracy</b>	±1.0°F (-22°F to 131°F) ±0.5°C (-30°C to 55°C); otherwise ±1.8°F (±1.0°C)
<b>Display Resolution</b>	0.1°F/°C
<b>Display Reading Update</b>	17 seconds
<b>Display Size</b>	1.92in W x 2.08in L (49mm W x 53mm L)
<b>Instrument Size</b>	2.99in W x 3.74in L x 0.74in D (76mm W x 95mm L x 19mm D)
<b>Body Casing</b>	ABS polymer, resistant to chemicals and high impact
<b>Sensor</b>	Thermistor
<b>External Probe Type/ Size</b>	Stainless Steel, 0.7in L x 0.2in Dia (17.8mm L x 5mm Dia)
<b>Sensor cable</b>	9.84ft x 0.08in Dia (3 meters x 2mm Dia)
<b>Battery</b>	AA Battery, user replaceable
<b>Certification / Calibration</b>	CE mark, NIST traceable, RoHS, WEEE



### Model 12217

- Minimum/Maximum memory for lowest and highest readings
- High and Low Alarms with audible buzzer and flashing red light
- Detachable external sensor with gold plated stereo jack connector
- Jumbo large LCD
- Selectable °C/°F temperature scales
- Blunt probe sensor with 10 foot (3 meter) cable
- Remaining battery indicator
- Non-volatile memory retains settings during battery swaps
- Mounts to vertical surfaces with strong built-in magnets
- Foldable stand for placement on flat surfaces